CERTIFICATE 0960-CPR-SKGIKOB.009758.03.ENG

Issued: 14-12-2020 Valid until: 14-12-2025 Replaces: 0960-CPR-SKGIKOB.009758.02.EN Issued: 13-10-2016



Certificateholder

B&B Locks bvba Uilenbaan 88 Unit 3 B-2160 Wommelgem T: +32 (0)332 636 30 E: info@bb-locks.com

I: www.bb-locks.com

Certificate of constancy of performance

Declaration of SKG-IKOB (Notified Body 0960)

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

EMERGENCY EXIT DEVICES OPERATED BY A LEVER HANDLE OR PUSH PAD FOR USE ON ESCAPE ROUTES

as specified in the attached appendix placed on the market under the name or trade mark of the holder of this certificate and produced by the holder of this certificate or for the holder of this certificate in the manufacturing plant(s) if mentioned above.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 179:2008

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 05-01-2016 and will remain valid until the date as mentioned at this certificate as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended of withdrawn by the notified product certification body.

For SKG-IKOB

ir. H.A.J. van Dartel Certification manager

The users of this certificate are advised to verify at www.skgikob.nl if this certificate is still valid and actual. This certificate consists of 2 pages.



SKG-IKOB Certificatie Poppenbouwing 56 4191 NZ Geldermalsen

Postbus 202 4190 CE Geldermalsen

T 088-2440100 info@skgikob.nl www.skgikob.nl

Appendix 1 CERTIFICATE OF CONSTANCY OF PERFORMANCE

Article	Specification	Classification according to EN 179										IFT - ITT (report nr.)	
Lock type: A1-3517 HX/HA/HE A1-3522 HX/HA/HE A1-6017 HX/HA/HE A1-6022 HX/HA/HE	Stainless steel, for 17 or 22 mm cylinder; Dimensions; 456x77x34 mm.	3	7	6	B	3	1	4	5	2	Α	В	
Locking plates: SSP1 SSP3 ASP1 ASP3	Stainless steel; Dimensions; 375x30x30,5 mm.												13-000057-PR05
Lever handles: SEH-17 SEH-22	Stainless steel, for 17 or 22 mm cylinder; Fixation; 2xM8.												