

Article nr:

A1BxxSA

SSP

ASP



xx = 25 (backset 25mm)

xx = 30 (backset 30mm)

xx = 35 (backset 35mm)

xx = 50 (backset 50mm)

xx = 60 (backset 60mm)


with standard striker plate:

A1BxxSA-SSP

with adjustable striker plate:

A1BxxSA-ASP

Connection diagram:



Technical characteristics:

Voltage	48V DC (min. 24V - max. 50V)
Consumption	60W (activation current) - 3.60W (permanent locking)
Principle	Fail safe (= unlocked without power)
Backset	available with backsets 25,30,35,50 and 60mm
Direction	Both L and R - symmetrical bolt for both bumper doors and revolving doors
Unlocking	Access control makes contact between pin 2 and 3 on the lock, the bolt retracts by spring force
Automatic locking	Electrically, each time the door closes
Panic function	There is no handle, so not according to EN 179
Signalisation	Position of the door (open/closed) and position of the bolt (unlocked/locked) as well as the use of the cylinder, transistors switch actively to GND (max. 24V DC / max. 100mA)
Resistance of the bolt	40'000N side load (measured directly on the bolt)
Throw of the bolt	20mm (in less than 100 milliseconds)
Temperature resistance range	-25°C to +70°C
Fire doors	Suitable for use in fire doors
Certification	EN 14846:2008 (classification 3 M 9 C 0 L 7 1 1)

General characteristics:

Superior quality electromechanical security lock working according to the fail-safe principle (= unlocked without power). The locks have been manufactured to be operated by different impulse generators: push buttons, numeric keypads, card readers, key contacts, timers, etc. These should be equipped with a Normally-Open contact. These locks are mortise locks suitable for both 17mm europrofile and 22mm round cylinders. The hardened duplex bolt, as well as the deadlock, are mounted on a solid baseplate. This baseplate is made of stainless steel (AISI 304, cast according to the lost-wax process). The stainless steel covers (AISI 304) provide a closed case. There are 2 stainless steel striker plates with closed striker cup (for extra protection of the bolt) available. The SSP striker plate has a fixed striker cup, which cannot be adjusted after installation. The ASP striker plate has an adjustable striker cup, which can be adjusted 2mm to the left and 2mm to the right any time after the installation.

The control system integrated in the lock provides for automatic locking when the door closes. The lock detects the striker plate by means of 3 Hall-sensors on the printed circuit board (which is protected against humidity etc. by a polyurethane casted resin). Subsequently, the bolt is ejected by a single acting solenoid and instantaneously blocked by the deadlock. The lock will now switch from activation current to holding current. To unlock, contact must be made between terminal clamps 2 and 3. Subsequently, the current to the solenoid is interrupted by the internal printed circuit board, causing the bolt to be retracted by means of springs. Using a cylinder the bolt can also be unlocked mechanically; in this case the current to the solenoid is also interrupted (via a microswitch on both the cylinder and the slider). After the door has been opened, the key must be turned back and removed from the cylinder. The bolt will remain retracted until the door closes and the striker plate has been detected (when no permanent contact is made between the 2 terminal clamps mentioned before). If the door is not opened after the unlocking impulse, the lock will automatically relock after 4 seconds. In case of power failure, the lock will remain in or go to the unlocked position.


Due to its symmetrical bolt, the door can be used both left and right. These locks are usually integrated in the door frame in order to avoid the use of a cable transfer (in this case, the striker plate is integrated in the door leaf). These locks can also be installed horizontally, with the bolt pointing downwards. This lock can be used in combination with automatic door openers. These electric locks should always get continuous power supply. That will ensure that they retain their intelligence and therefore will know their position.

Signalisation is provided with regard to the position of the bolt (locked - unlocked) and the position of the door (closed - open) as well as the use of the cylinder. These contacts switch to GND when activated (max. 24V DC / max. 100mA).

This lock model complies with the standard EN14846 (3 M 9 C 0 L 7 1 1) - certificate of constancy of performance 0960-CPR-SKGIKOB.009752.xx.ENG - DoP1011 (can be found on our website) and is furthermore suitable for high frequency use and can be activated continuously.

For the proper functioning of the lock it is important that the correct power and current arrives at the lock. Correct cable and power supply specifications must therefor be respected:

- cable: 2 x 1,5mm² (power cable) + 5 x 0,22mm² (signalisation wire); shielded (can be ordered separately with reference: **BB25LSZH**).
- power supply: 24V DC; 60W (per lock) stabilised power supply (can be ordered separately with reference: **PWR2-24**). The total distance between the lock and the power supply is limited to maximum 25m (this to avoid too large a drop in power supply on the cable).
- power supply: 48V DC; 60W (per lock) stabilised power supply (can be ordered separately with reference: **PWR2-48**). The total distance between the lock and the power supply is limited to maximum 300m (this to avoid too large a drop in power supply on the cable).

	B&B LOCKS bvba Uilenbaan 88 Unit 3 2160 Wommelgem Belgium						
	NB 0960 15						
	EN 14846:2008	3	M	9	C	0	L 7 1 1