



**B&B LOCKS bvba**  
**Declaration of Performance number: DOP1013**  
**EN 179:2008**  
**22/03/2023**

**MANUFACTURER:** B&B LOCKS bv  
Uilenbaan 88 Unit 3  
2160 Wommelgem  
Belgium

**NOTIFIED BODY:** SKG-IKOB, Geldermalsen NL  
NB 0960

Notified product certification body has performed ITT (Initial Type Testing), inspection of the manufacturing plant, FPC (Factory Production Control) and have issued the certificate of constancy of performance of the product.

**CERTIFICATE:** 0960-CPR-SKGIKOB.009758.xx.EN

**IFT - ITT (report nr.):** 13-000057-PR05

**PRODUCT AND DESCRIPTION:** A1 lock series with handle:  
**A1BxxyyHX, A1BxxyyHE**

In combination with one of the following lever handles:

**SEH-17**

**SEH-22**

Category of use	<b>3</b>	High frequency of use (little care + chance of incidence and misuse)
Durability	<b>7</b>	200'000 test cycles
Door mass	<b>6</b>	up to 200 Kg
Suitability for use on fire/smoke doors	<b>B</b>	Suitable for use on smoke/fire doors (EN1634-1)
Safety	<b>1</b>	Safety function
Corrosion resistance	<b>4</b>	240 h (very high resistance)
Security	<b>5</b>	5000 N
Projection of operating element	<b>2</b>	projection up to 100mm (standard projection)
Type of operation	<b>A</b>	Emergency exit device with "lever handle" operation
Field of door application	<b>B</b>	Outwardly opening single exit door only

The test program was chosen in such a way that all electro-mechanical locks built from the specification list below were covered. SKG-IKOB has established that all locks within this specification will meet the requirements and the classification above.

<u>Series</u>	<u>Signals</u>	<u>Backset xx</u>	<u>Cylinder yy</u>	<u>Function</u>	<u>extra signal</u>	<u>strike plate</u>
<b>A1</b>	<b>B</b>	<b>35</b>	<b>17</b>	<b>HX</b>	<b>- S</b>	<b>- SSP</b>
		<b>60</b>	<b>22</b>	<b>HE</b>		<b>ASP</b>



**B&B LOCKS bvba**  
**Declaration of Performance number: DOP1013**  
**EN 179:2008**  
**22/03/2023**

- B** Basic
- HX** Fail Secure - Locked without power - mechanical opening with cylinder from both sides and with handle from the secure side
- HE** Fail Secure - Locked without power (only when the door is closed) - mechanical opening with cylinder from both sides and with handle from the secure side
- S** Option: Potential free deadlock signal
- SSP** Standard Striker Plate with striker cup 3mm
- ASP** Adjustable Striker Plate with striker cup 6mm

Wommelgem, 22/03/2023  
On behalf of B&B LOCKS bv

---

Jack Boeckx  
Managing Director