



B&B LOCKS bvba
Declaration of Performance number: DOP1014
EN 1125:2008
22/03/2023

MANUFACTURER: B&B LOCKS bv
Uilenbaan 88 Unit 3
2160 Wommelgem
Belgium

NOTIFIED BODY: SKG-IKOB, Geldermalsen NL
NB 0960

Notified product certification body has performed ITT (Initial Type Testing), inspection of the manufacturing plant, FPC (Factory Production Control) and have issued the certificate of constancy of performance of the product.

CERTIFICATE: 0960-CPR-SKGIKOB.009760.xx.ENG
IFT - ITT (report nr.): 13-000057-PR06
SKG-IKOB (report nr.): 18.00121

PRODUCT AND DESCRIPTION: A1 lock series with handle:
A1BxxyyHX, A1BxxyyHE

In combination with Push-bar:

Push-bar **ECO EPN 900 II – IV**

Push-bar **ECO EPN 950**

Category of use	3	High frequency of use (little care + chance of incidence and misuse)
Durability	7	200'000 test cycles
Door mass	6	up to 200 Kg
Suitebility for use on fire/smoke doors	B	Suitable for use on smoke/fire doors (EN1634-1)
Safety	1	Safety function
Corrosion resistance	4	240 h (very high resistance)
Security	2	Grade 2, only one grade
Projection of the horizontal bar	2	projection up to 100mm (standard projection)
Type of horizontal bar operation	A	Panic exit device with "push-bar" operation
Field of door application	B	Single door only

In combination with Touch-bar:

Touch-bar **ECO EPN 2000 II**

Category of use	3	High frequency of use (little care + chance of incidence and misuse)
Durability	7	200'000 test cycles
Door mass	6	up to 200 Kg
Suitebility for use on fire/smoke doors	B	Suitable for use on smoke/fire doors (EN1634-1)
Safety	1	Safety function
Corrosion resistance	4	240 h (very high resistance)
Security	2	Grade 2, only one grade
Projection of the horizontal bar	2	projection up to 100mm (standard projection)
Type of horizontal bar operation	B	Panic exit device with "touch-bar" operation
Field of door application	B	Single door only



B&B LOCKS bvba
Declaration of Performance number: **DOP1014**
EN 1125:2008
22/03/2023

The test program was chosen in such a way that all electro-mechanical locks built from the specification list below were covered. SKG-IKOB has established that all locks within this specification will meet the requirements and the classification above.

<u>Series</u>	<u>Signals</u>	<u>Backset xx</u>	<u>Cylinder yy</u>	<u>Function</u>	<u>extra signal</u>	<u>strike plate</u>
A1	B	35	17	HX	- S	- SSP
		60	22	HE		ASP

- B** Basic
- HX** Fail Secure - Locked without power - mechanical opening with cylinder from both sides and with handle from the secure side
- HE** Fail Secure - Locked without power (only when the door is closed) - mechanical opening with cylinder from both sides and with handle from the secure side
- S** Option: Potential free deadlock signal
- SSP** Standard Striker Plate with striker cup 3mm
- ASP** Adjustable Striker Plate with striker cup 6mm

Wommelgem, 22/03/2023
On behalf of B&B LOCKS bv

Jack Boeckx
Managing Director